## 2025 THOMPSON SPEEDWAY CROWN VIC CLASS RULES & SPECIFICATIONS

Cars: 1993 & Up Ford Crown Vic, Grand Marquis, Town Cars only

4.6 L SOHC only Motor. MUST remain stock to include all drive pulleys and belts

(no removing ac or any pulleys from factory stock)

Wheels: Stock Steel (NO aluminum Wheels)

1-inch lug nuts are recommended

No wheel spacers

No offset wheels on 2003 – up

17 inch Dodge Charger wheels allowed on 2002 – older

Roll Cage: Minimum 4 point cage with 4 door bars on Driver's side

(No straight bars on driver's side)

1 3/4 diameter .095 thickness. Cages can be installed by any welder but must pass track inspection before it can be raced. Cage must be welded to frame not

floor pan.

Body: All panels MUST be stock

Gutting only allowed on drivers door – NOT GUTTING of any other panels

All panels must stick with magnet Mirrors are highly recommended

Factory Frame: No stiffening/modifications to the factory frame

Suspension: No cutting, heating or loweing of spring. No altering of suspension or springs.

No spacers of any kind.

Exhaust: Pipes must go behind driver or out to the side and have a muffler.

Tires: NO high-performance tires or directional tires allowed – No autocross tires

All season tires: 400 treadwear or higher

Required tire sizes: 235/55/17

225/60/16 215/70/15

Sway Bars Links: Stock front and rear, must be same length, must be operational

<sup>\*</sup>No tire treatment or softener of any kind

<sup>\*</sup>No Firehawks, no Goodyear RSA

Air Filter: Unaltered airbus, must have OE compatible air filter with filter media

Manifold: Stock

Bumpers: Stock, no fabricated bumpers

Bumper hoops must be welded to bumper only, not to frame

OEM covers from any type of vehicle (front and rear bumper covers not

required)

Shocks & Spring: Stock or OEM replacements (can cut 2" holes above rear shocks to access

top shock nut) May run two 1" spring rubber in right front only.

Factory Gear Only: 2.73, 3.27, 3.55 and 3.73 ratio only

Steering Column: Stock with quick disconnect is allowed

Must be secured to original dash skeleton

Windshield: Must be stock

Caster & Camber: You may adjust as factory adjustments allow. No other suspension

modifications allowed. Max/Min camber number to be determined

Max Camber 1.5 inches measured at the wheel.

Dash: Must be original, air bags must be removed

All unnecessary and unused wires may be removed

HVAC box must remain in stock location. If removed weight penalty or Battery

must be mounted in the location of heater box

Must have working OBDII connector, must be sealed during each feature

event

Dash pads are not required

Weight: No added weight

Battery: Can be relocated but must be secured in box, terminals must be covered

Pedals: Stock

No Air Ride

Computers: Have to be stock/no modifications or tuning and no plug-in devices (pedal

commander, dash pods or plug and play tuners)

Raceiver highly recommended. WILL be mandatory in 2025. No 2 way radios

The top 5 finishers will be teched after each event is completed. Driver and Crew Chief only at the car during inspection

Track Claim \$3500. Thompson Speedway can claim any car from any race at any time. Refusal of claim will result in disqualification from the event and a one year suspension from racing at Thompson Speedway.

## Safety Rules:

Head and neck restraints (Hans) or equivalent mandatory

Five Point Safety Belts, which must be 3 years or newer, in good condition, properly mounted. Full containment is strongly recommended, as re leg restraints, wings and braces.

Fuel Kill Switch in rear of deck or behind driver's roll cage or kill all switch if battery is relocated, must be labeled On/Off

Window nets are mandatory and must be attached to the cage

Full face helmet, Snell approved and in good condition

Driver's uniform and gloves must be Nomex and in good condition and clean

It is your responsibility to see that your car is legal. No equipment will be considered as having been approved by reason of having passed through tech unobserved.

In keeping with Thompson Speedway's commitment to maintaining proper balance in the competition arena, it may be necessary of Thompson to make rules changes and or rule modifications from time to time. Such changes are designed to enhance close competition. For competitive balance, Thompson Speedway reserves the right to change, modify or delete or add to any guidelines as deemed necessary throughout the season.

All rules subject to interpretation of Thompson Speedway Officials.